



White Paper

WP_001

Connecting Peripherals to an Android Platform

Version 1.0

Issue Date: 2012-02-09

This white paper will describe some of the options for connecting peripheral accessories to Android OS based tablets/phones. The main focus will be the use of the Android Open Accessory Initiative.

Use of FTDI devices in life support and/or safety applications is entirely at the user's risk, and the user agrees to defend, indemnify and hold FTDI harmless from any and all damages, claims, suits or expense resulting from such use.

Future Technology Devices International Limited (FTDI)

Unit 1, 2 Seaward Place, Glasgow G41 1HH, United Kingdom

Tel.: +44 (0) 141 429 2777 Fax: + 44 (0) 141 429 2758

Web Site: <http://ftdichip.com>

Copyright © 2012 Future Technology Devices International Limited

Table of Contents

1	Introduction	2
1.1	What is Android?	2
1.2	Connecting peripherals.....	2
2	Android Open Accessory Mode	3
2.1	What is Android Open Accessory Mode?	3
2.2	How a peripheral attaches to an Android in Open Accessory Mode.....	3
3	Software Applications	5
3.1	Connecting the software application to the hardware.....	5
3.2	Data consuming applications	5
3.3	Data producing applications	5
4	Summary	6
5	Contact Information.....	7
	Appendix A – References	8
	Document References.....	8
	Acronyms and Abbreviations	8
	Appendix B – List of Tables & Figures	9
	List of Tables	9
	No table of figures entries found.....	9
	List of Figures	9
	Appendix C – Revision History	10

1 Introduction

This white paper will describe some of the options for connecting peripheral accessories to Android OS based tablets/phones. The main focus will be the use of the Android Open Accessory Initiative.

1.1 What is Android?

Android is a Linux based operating system that is becoming very popular in mobile devices such as phones and tablets. The processor in current generation Android platforms is typically ARM based with the OS being optimised to support the hardware on the platform. This means the minimum required drivers to support the platform hardware are included in the OS which is often locked by the device supplier to prevent users customising their OS. The OS is regularly updated with many new features being added with each release. Figure 1 shows the historical progression of Android releases.

2008	2009	2009	2009	2009	2010	2010	2011	2011
V1.0	V1.1	V1.5	V1.6	V2.0	V2.2	V2.3.x	V3.x	V4.x
		Cupcake	Donut	Eclair	Froyo	Ginger Bread	Honey-comb	Ice Cream Sandwich

Figure 1.1 Android OS releases

1.2 Connecting peripherals

With mobile phones the concept of connecting peripheral accessories was rarely considered, but with tablets this is less likely to be the case. In “conventional” hardware such as laptops and desktops, there will be a wide variety of connectors and driver support for connecting peripherals such as mice, printers etc. With the mobile tablet where size, weight and power consumption are critical concerns there are less likely to be all these connectors available.

Many Android platforms are now supplied with On The Go (OTG) USB ports, allowing for the USB port to be either a host or a device. Some of these OTG ports will be USB device only i.e. they can only connect to a USB host as a USB device.

Some of the newer generation devices will be full OTG offering host and device capabilities. However the potential issue with the host port is that a particular peripheral may require a special driver to be loaded which may mean the owner of the platform has to ROOT their device to get the permissions to allow access for installing new drivers.

Rooting a device may invalidate a manufacturer’s warranty and is not really a task that a typical consumer could/should be expected to perform.

Fortunately from version 3.1 (Honeycomb) onwards Android have provided a new and novel solution to the problem, called Android Open Accessory Mode. Features

2 Android Open Accessory Mode

2.1 What is Android Open Accessory Mode?

Android Open Accessory Mode allows for connecting peripherals to an Android platform where the Android is the USB device and the peripheral (accessory) is the USB host. This is the complete reverse of conventional interconnect.

This game changing approach to attaching peripherals allows for 3 key advantages:

- No need to develop special drivers for the hardware.
- No need to root devices to alter permissions for loading drivers.
- The power to use the port is provided by the peripheral ensuring the mobile device battery is not drained faster by the external hardware being attached.




Figure 2.1 Android Open Accessory Mode Connection

2.2 How a peripheral attaches to an Android in Open Accessory Mode

To connect to an Android platform in Open Accessory Mode the platform must first support the mode.

This is true of OS version 3.1 onwards, but may also be available on OS versions as far back as 2.3.4 if the OEM has back ported the feature to this OS version.

When an Open Accessory device is connected to the Android it must send a vendor request to the Android to enquire if the device supports Open Accessory Mode. This is the Get_Protocol command.

If the reply is no then the communication stops there. However, if the reply is yes then the peripheral sends its own unique descriptor strings to identify itself. There is then another USB vendor request to enable the Open Accessory Mode and re-enumerate the Android device in this configuration.

When enumerated as an Open Accessory Mode device there will be one USB BULK IN endpoint and one USB BULK OUT endpoint as well as the control endpoint.

This interface will be full speed (12Mbit/s) USB allowing for data transfer in and out.




Figure 2.2 Android Open Accessory Mode Enabling

3 Software Applications

3.1 Connecting the software application to the hardware

Typically an application will connect to hardware via drivers. However Android Open Accessory Mode does not require users to install extra drivers.

Each Open Accessory Mode USB host has a set of string descriptors that the Android OS is capable of reading. These strings will match an application on the Android OS. The application then uses these strings to auto start the application when the hardware is connected.

The strings that must be sent are:

Manufacturer: Used to declare the peripheral manufacturer.

Model: Used to declare the hardware model.

Version: Used to provide a version number for the peripheral.

Additional identifier strings may also be sent:

description: Used to provide a descriptive name for the peripheral

uri: Used to provide a URL for obtaining more information from the internet. If no installed application matches the strings supplied, the OS will display a message box with a link to the web site specified in the URI string (if supplied).

serial: Used to provide a serial number for the peripheral

3.2 Data consuming applications

The Android OS is a full OS with ever increasing processing capabilities. Making full use of this power can be realised by adding peripherals to the basic Android device such as temperature sensors, pressure sensors and CANBus engine management controllers that will provide raw data to be processed on the Android platform itself.

3.3 Data producing applications

The flip side to receiving lots of data for offline processing is to be a data producer controlling hardware. A typical example may be to send data to a printer to obtain hard copies of data or to make use of the GPS capabilities of the Android platform to then control a robot and move it into position.

4 Summary

Android powered devices are so much more than just mobile phones. Unleashing the full potential is about adding peripherals (accessories) to the basic mobile device. By making use of the Open Accessory Mode, the development is simplified (no drivers) and the battery life is not compromised either as the peripheral must provide the power. There are already a few manufacturers waking up to this possibility, including FTDI, who want to make connectivity to the mobile platforms a reality and Open Accessory Mode may just be the future, delivered now.

5 Contact Information

Head Office – Glasgow, UK

Future Technology Devices International Limited
Unit 1, 2 Seaward Place, Centurion Business Park
Glasgow G41 1HH
United Kingdom
Tel: +44 (0) 141 429 2777
Fax: +44 (0) 141 429 2758

E-mail (Sales) sales1@ftdichip.com
E-mail (Support) support1@ftdichip.com
E-mail (General Enquiries) admin1@ftdichip.com

Branch Office – Hillsboro, Oregon, USA

Future Technology Devices International Limited
(USA)
7235 NW Evergreen Parkway, Suite 600
Hillsboro, OR 97123-5803
USA
Tel: +1 (503) 547 0988
Fax: +1 (503) 547 0987

E-Mail (Sales) us.sales@ftdichip.com
E-Mail (Support) us.support@ftdichip.com
E-Mail (General Enquiries) us.admin@ftdichip.com

Branch Office – Taipei, Taiwan

Future Technology Devices International Limited
(Taiwan)
2F, No. 516, Sec. 1, NeiHu Road
Taipei 114
Taiwan, R.O.C.
Tel: +886 (0) 2 8791 3570
Fax: +886 (0) 2 8791 3576

E-mail (Sales) tw.sales1@ftdichip.com
E-mail (Support) tw.support1@ftdichip.com
E-mail (General Enquiries) tw.admin1@ftdichip.com

Branch Office – Shanghai, China

Future Technology Devices International Limited
(China)
Room 408, 317 Xianxia Road,
Shanghai, 200051
China
Tel: +86 21 62351596
Fax: +86 21 62351595

E-mail (Sales) cn.sales@ftdichip.com
E-mail (Support) cn.support@ftdichip.com
E-mail (General Enquiries) cn.admin@ftdichip.com

Web Site

<http://ftdichip.com>

System and equipment manufacturers and designers are responsible to ensure that their systems, and any Future Technology Devices International Ltd (FTDI) devices incorporated in their systems, meet all applicable safety, regulatory and system-level performance requirements. All application-related information in this document (including application descriptions, suggested FTDI devices and other materials) is provided for reference only. While FTDI has taken care to assure it is accurate, this information is subject to customer confirmation, and FTDI disclaims all liability for system designs and for any applications assistance provided by FTDI. Use of FTDI devices in life support and/or safety applications is entirely at the user's risk, and the user agrees to defend, indemnify and hold harmless FTDI from any and all damages, claims, suits or expense resulting from such use. This document is subject to change without notice. No freedom to use patents or other intellectual property rights is implied by the publication of this document. Neither the whole nor any part of the information contained in, or the product described in this document, may be adapted or reproduced in any material or electronic form without the prior written consent of the copyright holder. Future Technology Devices International Ltd, Unit 1, 2 Seaward Place, Centurion Business Park, Glasgow G41 1HH, United Kingdom. Scotland Registered Company Number: SC136640

Appendix A – References

Document References

Replace this text. List FTDI and external datasheets, application notes, website links and other documents. Notice the hyperlink in the example.

[AN 146 USB Hardware Design Guides for FTDI ICs](#)

Acronyms and Abbreviations

Terms	Description
USB	Universal Serial Bus
USB-IF	USB Implementers Forum

Appendix B – List of Tables & Figures

List of Tables

No table of figures entries found.

List of Figures

Figure 1.1 Android OS releases	2
Figure 2.1 Android Open Accessory Mode Connection	3
Figure 2.2 Android Open Accessory Mode Enabling	4

Appendix C – Revision History

Document Title: WP_001 Connecting Peripherals to an Android Platform
Document Reference No.: FT_000633
Clearance No.: FTDI# 279
Product Page: <http://www.ftdichip.com/FTProducts.htm>
Document Feedback: [Send Feedback](#)

Revision	Changes	Date
1.0	Initial Release	2012-02-09